

ARIES-2™

HIGH POWER, FIXED WAVELENGTH

DRS Daylight's years of experience and field-proven performance in high-power mid-IR lasers come together in the Aries-2 family of products. The Aries-2 is a fixed-wavelength, high-power laser that offers a user-specified center wavelength and output power up to 2 W. Aries-2 provides CW or pulsed operation with internal or external amplitude modulation. It is CDRH compliant and is CE certified.

All Aries-2 systems come with a SideKick™ laser controller and a GUI and SDK to give you everything you need for productivity out of the box.

HIGHLIGHTS

- Optical power of up to 2 W
- Center wavelength choices include 4.0, 4.6, 8.7, 9.1, and 10.5 μm
- CW or pulsed output
- Superb TEM_{00} beam quality allows fiber coupling
- Superior power stability (< 2% rms, 1 hr)
- Amplitude modulation up to 1 MHz
- SideKick™ controller, GUI, and SDK included with all systems
- Proprietary HFQD™ circuitry to protect your chips

HIGH POWER, FIXED WAVELENGTH

APPLICATIONS

- Stand-Off Explosive Detection
- Chemical Agent Detection
- Infrared Detector Testing
- Multispectral Active Imaging
- Infrared Countermeasures
- Free-Space Communications
- Infrared Scene Generation
- Optical Fiber Testing

SPECIFICATIONS

OPERATION MODE	
Pulsed or CW	

SPECIFICATIONS	
Center Wavelength Availability	4-11 μm^*
Spatial Mode	TEM ₀₀ (nominal)
Beam Divergence	< 4 mrad** (full angle, 1/e ² intensity width)
Beam Diameter	< 5 mm (1/e ² intensity width)
Ellipticity	< 1.5
Pulse Repetition Frequency	CW to 1 MHz
Rise/Fall Time (10-90%)	< 100 ns
QCL Compliance Voltage	< 17 VDC
QCL Operating Current	< 3 A
Operating Range (Case Temp)	15 - 55 °C
Dimensions (LxWxH)	14 x 7 x 8.6 cm

PERFORMANCE EXAMPLES	
Center Wavelength (μm)	Optical Power (W)
4.0	1.0
4.6	2.0
8.7	0.5
9.1	1.0
10.5	0.3


* Call for specific wavelength availability

** Measured at 4 μm ; scales with wavelength - please inquire


Forced air and liquid cooling accessories required for higher duty cycles

Water cooling required for CW operation or pulsed duty cycles > 5%

BEAM PROFILE



POWER CURVE



INVISIBLE LASER RADIATION
AVOID EYE OR SKIN EXPOSURE TO
DIRECT OR SCATTERED RADIATION
CLASS 4 LASER PRODUCT



COMPLIES WITH 21 CFR 1040.10 AND 1040.11 EXCEPT FOR DEVIATIONS PURSUANT TO LASER NOTICE NO. 50, DATED JUNE 24, 2007. COMPLIES WITH IEC 60825-01

The information in this data sheet is to the best of our knowledge, accurate as of the date of issue. Leonardo DRS reserves the right to change this information without notice. Nothing herein shall be deemed to create any warranty, expressed or implied. Copyright © Daylight Solutions 2021 All Rights Reserved.

REV 7-2021



DRS Daylight Solutions
16465 Via Esprillo
San Diego, CA 92127
Tel. +1 858 432 7500

daylightsolutions.com